COMFORT DRIVE SAE 20W50 API SG/CD ACEA A2/B2



Description

BENZOL® Comfort Drive SAE 20W50 API SG/CD is a multifunctional heavy-duty lubricant designed specifically to meet wide range of passenger car engines and light industrial vehicles. It can be used in city, road and highway, during all seasons. The product is formulated with high quality base stocks and balanced additive system to provide high level of engine protection and performance



Applications

BENZOL® Mineral SAE 20W50 Engine Oil is recommended for passenger cars, light trucks SUV's and vans, gasoline powered equipment, moderate duty LPG engines and four strokes' motorcycles engines under the most severe and varied operating conditions.

Specifications and Approvals

API SG/CD, ACEA A2/B2, JASO MA

Technical Specifications

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	L2.5
Density @ 15 °C, Kg/L	D-1298	0.8822
Viscosity @ 100 °C, cst	D-445	19.75
Viscosity @ 40 °C, cst	D-445	185.9
Viscosity index	D-2270	123
Flash Point, °C (COC)	D-92	241
Pour Point, °C	D-97	-23
Foam SEQ.I/II/III	D-892	0/0/0
TBN, mg KOH/g	D-2896	5.5
CCS at -15°C (mPa s)	D-5293	8570

Performance Benefits

- Improved control of volatility and oil consumption.
- Protects against soot, varnish, and sludge formation.
- Highly effective control over wear, corrosion and rust.
- Exceptional resistance to oxidation and foaming.
- Excellent dispersive and detergent properties which ensure a clean engine.

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit www.benzollubricants.de

