

2T RACER LITE SAE 20 API TC JASO FC



Description

BENZOL® Racer Lite SAE 20 API TC is particularly recommended as a lubricant for 2-stroke scooter engines up to 125 cc's. This oil is particularly suited to the demands of urban traffic (stop & go) and journeys in rural conditions (intercity). It is compatible with leadless fuel oil level should comply with the vehicle manufacturer's recommendations.



Applications

BENZOL® is developed for two-stroke engines operating under a range of varied conditions. It is recommended for use in the applications for air-cooled 2-stroke engines light motorbikes and scooters.

Specifications and Approvals

API TC, JASO FC, ISO-L-EGD.

Technical Specifications

Performance Benefits

- Deposit Control Formula.
- Ensures fast and reliable starting.
- Protects against the build-up of carbon deposits on the piston and spark plug.
- Protection against pre-ignition problems.
- Thermal and oxidation stability.

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	Green/Blue
Density @ 15 °C, kg/L	D-1298	0.8785
Viscosity @ 100 °C, cSt	D-445	9.12
Viscosity @ 40 °C, cSt	D-445	66.02
Viscosity index	D-2270	115
Flash Point, °C (COC)	D-92	208
Pour Point, °C	D-97	-24
Foam SEQ.I/II/III	D-892	0/0/0
TBN, mg KOH/g	D-2896	4.1

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit www.benzollubricants.de

