

4T MOTO RACER SAE 20W40 API SL JASO MA2



Description

BENZOL® 4T Moto Racer 20W40 API SL JASO MA2 is a premium performance, shear-stable, multi-grade gasoline engine oil specifically designed for use in four-stroke motorcycles and portable power equipment requiring API SL JASO MA/MA2 Lubricants, including high output engines operating in severe service.



Applications

BENZOL® 4T Moto Racer is used for motorcycles and scooters in city traffic. It is suitable for all types of four stroke motorcycles where JASO MA2 performance is recommended.

Performance Benefits

- Improved control of sludge and oil thickening
- Vastly improved protection of gears.
- Exceptional thermo-oxidative stability.
- Complies with requirements of catalyst equipped engines.
- High friction factor prevents clutch slippage and disc wear.

Specifications and Approvals

API SL, JASO MA2

Technical Specifications

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	L2.5
Density @ 15 °C, kg/L	D-1298	0.8810
Viscosity @ 100 °C, cSt	D-445	14.55
Viscosity @ 40 °C, cSt	D-445	114.6
Viscosity index	D-2270	130
Flash Point, °C (COC)	D-92	238
Pour Point, °C	D-97	-25
Foam SEQ.I/II/III	D-892	0/0/0
TBN, mg KOH/g	D-2896	6.2
CCS at -15°C (mPa.s)	D-5293	8790

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit www.benzollubricants.de

