

4T MOTO RACER SAE 20W50 API SN JASO MA2



Description

BENZOL® 4T Moto Racer 20W50 API SN is a premium performance, shear-stable, multi-grade gasoline engine oil specifically designed for use in four-stroke motorcycles and portable power equipment requiring API SN JASO MA2 Lubricants, including high output engines operating in severe service.



Applications

BENZOL® 4T Moto Racer is used for motorcycles and scooters in city traffic. It is suitable for all types of four stroke motorcycles where JASO MA2 performance is recommended.

Specifications and Approvals

API SN, JASO MA2.

Performance Benefits

- The trials in four-stroke motorcycles under extreme working Conditions have confirmed excellent protection against wear.
- Ensures full protection for the engine.
- Exceptional thermo-oxidative stability.
- Great durability at high temperature.
- Quick engine response and improved power output and increased reliability.

Technical Specifications

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	L2.5
Density @ 15 °C, kg/L	D-1298	0.8822
Viscosity @ 100 °C, cSt	D-445	19.50
Viscosity @ 40 °C, cSt	D-445	169.1
Viscosity index	D-2270	133
Flash Point, °C (COC)	D-92	236
Pour Point, °C	D-97	-26
Foam SEQ.I/II/III	D-892	0/0/0
TBN, mg KOH/g	D-2896	7.8
CCS at -15°C (mPa.s)	D-5293	8500

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit www.benzollubricants.de

