

SHPD FLEET TURBO SAE 20W60 API CH-4/SL ACEA E5



Description

BENZOL® SHPD Fleet Turbo SAE 20W60 is a superior quality heavy-duty lubricant for diesel engines. It is blended from premium quality virgin base oils and advanced additives that offer the best possible lubrication. It assures excellent protection against high temperature engine deposits, oil degradation, and forms a thick oil film that protects engine parts from friction and wear.



Applications

BENZOL® SHPD Fleet Turbo can be used in older trucks and buses as well as for cost effective lubrication in off-highway applications such as agricultural tractors.

Specifications and Approvals

API CH-4/SL, ACEA E5.

Technical Specifications

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	2.5
Density @ 15 °C, kg/L	D-1298	0.8880
Viscosity @ 100 °C, cSt	D-445	24.50
Viscosity @ 40 °C, cSt	D-445	259.7
Viscosity index	D-2270	120
Flash Point, °C (COC)	D-92	244
Pour Point, °C	D-97	-22
Foam SEQ.I/II/III	D-892	0/0/0
TBN, mg KOH/g	D-2896	11.5

Performance Benefits

- Excellent protection against piston deposits.
- Controls engine wear.
- Good oxidation and thermal stability.
- Excellent engine cleanliness and wear protection.
- Maintains engine power and efficiency and lowers servicing costs.

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit www.benzollubricants.de

