# **MODERN DRIVE SAE 0W16 API SN ILSAC GF-6B**



### Description

BENZOL® Modern Drive SAE 0W16 API SN is a PAO (Polyalphaolefin) based, fully synthetic low friction motor oil of the latest generation recommended for the lubrication of gasoline engines. API SN technology ensures maximum resistance to low-speed pre-ignition (LSPI) events for long service life in modern direct injected high-output engines. These oils are specifically formulated to provide high level of fuel efficiency and deposit protection under severe service conditions.



### **Applications**

BENZOL® Fully Synthetic SAE 0W16 Engine Oil is recommended for passenger cars, light trucks, gasoline powered equipment and hybrid engines. For all-season use in engines operating on gasoline, high-ethanol gasoline and with or without turbo-charging and direct injection.

#### **Specifications and Approvals**

API SN and RC (RESOURCE CONSERVING), API SN plus and RC, ILSAC GF-6B, GM dexos1™ Gen 2

## **Technical Specifications**

#### **Performance Benefits**

- Low viscosity, advanced full synthetic formula.
- Outstanding low temperature capabilities.
- Can clean up sludge left behind in your engine.
- Exceptional resistance to oxidation and foaming.
- Excellent dispersive and detergent properties ensuring a clean engine.
- Improved protection during start-up by maintaining protective oil films.

Product/Pa	rt Number			
MD01600333	4 x 5	MD01600323	4 x 4	
MD01600173	12 x 1	MD01600173	24 X 1	
MD01600513	1 x 20	MD01600533	1 x 25	
MD01600563	1 x 200	MD01600573	1 x 208	
MD01600603	1×1000			

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	L3.0
Density @ 15 °C, kg/l	D-1298	0.8420
Viscosity @ 100 °C, cSt	D-445	7.20
Viscosity @ 40 °C, cSt	D-445	35.90
Viscosity index	D-2270	169
Flash Point, °C (COC)	D-92	224
Pour Point, °C	D-97	-45
Foam SEQ.I/II/III	D-892	0/0/0
TBN, mg KOH/g	D-2896	7.6
CCS at -35°C (mPa.s)	D-5293	5600
Sulphated Ash(mass%)	D-874	0.80
Sulphur Content (mass%)	D-4294	0.28
Phosphorus (P) (mass%)	D-5185	0.075
HTHS at 150°C (mPa.s)	D-5481	2.5

#### **HEALTH AND SAFETY**

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit <a href="https://www.benzollubricants.de">www.benzollubricants.de</a>

