

EFFICIENT DRIVE SAE 10W30 API SL/CF ACEA A3/B4



Description

BENZOL® Efficient Drive SAE 10W30 API SL/CF is a high range quality lubricant, synthetic, specially formulated to meet the latest performance requirements of modern engines. It can be used in city, road and highway, under extreme conditions in all seasons.



Applications

BENZOL® Synthetic SAE 10W30 Engine Oil is recommended for passenger cars, light trucks, gasoline powered equipment and four strokes' motorcycles engines under the most severe and varied operating conditions.

Specifications and Approvals

API SL/CF ACEA A3/B4, JASO MA2, MB 229.1, VW 501.00/505.00, RN 0700/0710

Technical Specifications

Performance Benefits

- Enhanced fuel economy properties.
- Excellent anti-wear characteristics.
- Excellent low temperature capabilities.
- Increase engine efficiency.

Product/Part Number

ED09424332	4 x 5	ED09424322	4 x 4
ED09424172	12 x 1	ED09424172	24 X 1
ED09424512	1 x 20	ED09424532	1 x 25
ED09424562	1 x 200	ED09424572	1 x 208
ED09424602	1x1000		

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	L2.5
Density @ 15 °C, kg/L	D-1298	0.8720
Viscosity @ 100 °C, cSt	D-445	10.50
Viscosity @ 40 °C, cSt	D-445	69.95
Viscosity index	D-2270	138
Flash Point, °C (COC)	D-92	232
Pour Point, °C	D-97	-36
Foam SEQ.I/II/III	D-892	0/0/0
TBN, mg KOH/g	D-2896	10.1
CCS at -25°C (mPa.s)	D-5293	6400

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit www.benzollubricants.de

