

EFFICIENT DRIVE SAE 10W40 API SL/CF ACEA A3/B4



Description

BENZOL® Efficient Drive SAE 10W40 API SL/CF is a high range quality lubricant, synthetic, specially formulated to meet the latest performance requirements of modern engines. It can be used in city, road and highway, under extreme conditions in all seasons.



Applications

BENZOL® Synthetic SAE 10W40 Engine Oil is recommended for passenger cars, light trucks, gasoline powered equipment and four strokes' motorcycles engines under the most severe and varied operating conditions.

Specifications and Approvals

API SL/CF, ACEA A3/B4, JASO MA2, MB 228.1/229.1, PSA B71 2294, VW 501.00/505.00, FIAT 9.55535-D2/G2, RN 0700/0710

Technical Specifications

Performance Benefits

- Enhanced fuel economy properties.
- Excellent anti-wear characteristics.
- Excellent low temperature capabilities.
- Increase engine efficiency.
- Advanced synthetic formula

Product/Part Number

ED10424332	4 x 5	ED10424322	4 x 4
ED10424172	12 x 1	ED10424172	24 X 1
ED10424512	1 x 20	ED10424532	1 x 25
ED10424562	1 x 200	ED10424572	1 x 208
ED10424602	1x1000		

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	L2.5
Density @ 15 °C, kg/L	D-1298	0.8725
Viscosity @ 100 °C, cSt	D-445	14.60
Viscosity @ 40 °C, cSt	D-445	110.6
Viscosity index	D-2270	136
Flash Point, °C (COC)	D-92	236
Pour Point, °C	D-97	-33
Foam SEQ.I/II/III	D-892	0/0/0
TBN, mg KOH/g	D-2896	10.1
CCS at -25°C (mPa.s)	D-5293	6600

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit www.benzollubricants.de

