

MODERN DRIVE SAE 5W30 API SP ILSAC GF-6A



Description

BENZOL® Modern Drive SAE 5W30 API SP is a fully synthetic low friction motor oil of the latest generation recommended for the lubrication of gasoline engines. API SP technology ensures maximum resistance to low-speed pre-ignition (LSPI) events for long service life in modern direct injected high-output engines. These oils are specifically formulated to provide high level of fuel efficiency and deposit protection under severe service conditions.



Applications

BENZOL® Fully Synthetic SAE 5W30 Engine Oil is recommended for passenger cars, light trucks, gasoline powered equipment and hybrid engines. For all-season use in engines operating on gasoline, high-ethanol gasoline and without turbo-charging and direct injection.

Specifications and Approvals

API SP and RC, API SN plus and RC, ILSAC GF-6A, GM dexos1™ Gen 2, GM 6094M, Chrysler MS6395, Ford WSS-M2C946-B1 / WSS-M2C946-A /WSS-M2C929-A

Technical Specifications

Performance Benefits

- Low viscosity, advanced full synthetic formula.
- Outstanding low temperature capabilities.
- Can clean up sludge left behind in your engine.
- Exceptional resistance to oxidation and foaming.
- Excellent dispersive and detergent properties ensuring a clean engine.
- Improved protection during start-up by maintaining protective oil film.
- Superior fuel economy and CO2 reduction.

Product/Part Number

MD06800333	4 x 5	MD06800323	4 x 4
MD06800173	12 x 1	MD06800173	24 X 1
MD06800513	1 x 20	MD06800533	1 x 25
MD06800563	1 x 200	MD06800573	1 x 208
MD06800603	1x1000		

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	L3.0
Density @ 15 °C, kg/L	D-1298	0.8618
Viscosity @ 100 °C, cSt	D-445	11.20
Viscosity @ 40 °C, cSt	D-445	60.20
Viscosity index	D-2270	160
Flash Point, °C (COC)	D-92	224
Pour Point, °C	D-97	-39
Foam SEQ.I/II/III	D-892	0/0/0
TBN, mg KOH/g	D-2896	7.2
CCS at -30°C (mPa.s)	D-5293	6200
Sulphated Ash(mass%)	D-874	0.75
Sulphur Content (mass%)	D-4294	0.30
Phosphorus (P) (mass%)	D-5185	0.072
HTHS at 150°C (mPa.s)	D-5481	2.94

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit www.benzollubricants.de

