MODERN DRIVE SAE 5W30 API SN/CF ACEA A5/B5



Description

BENZOL® Modern Drive SAE 5W30 API SN/CF is a high range quality lubricant, fully synthetic, specially formulated to meet the latest performance requirements of modern engines. It can be used in city, road, and highway, under extreme conditions in all seasons.



Applications

BENZOL® Fully Synthetic SAE 5W30 Engine Oil is recommended for passenger cars, light trucks, gasoline powered equipment engines. For all-season use in engines operating on gasoline, high-ethanol gasoline and without turbo-charging and direct injection.

Specifications and Approvals

API SN/CF, ACEA A5/B5, MB-Approval 229.51/229.52, VW 504.00/507.00, BMW LL-04, GM Dexos 2, PORSCHE C30, RN 0700/0710, Fiat 9.55535-S3, WSS-M2C913-D, PSA B71 2290; PSA B71 2297

Performance Benefits

- Enhanced fuel economy properties.
- Excellent anti-wear characteristics.
- Excellent low temperature capabilities.
- Increase engine efficiency.
- Advanced synthetic formula.

Product/Part Number

MD06 <mark>625333</mark>	4 x 5	MD06625333	4 x 4
MD06625173	12 x 1	MD06625173	24 X 1
MD06625513	1 x 20	MD06625533	1 x 25
MD06625563	1 x 200	MD06625573	1 x 208
MD06625603	1x1000		

Technical Specifications

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	L3.0
Density @ 15 °C, kg/L	D-1298	0.8513
Viscosity @ 100 °C, cSt	D-445	10.92
Viscosity @ 40 °C, cSt	D-445	64.02
Viscosity index	D-2270	164
Flash Point, °C (COC)	D-92	224
Pour Point, °C	D-97	-36
Foam SEQ.I/II/III	D-892	0/0/0
TBN, mg KOH/g	D-2896	8.3
CCS at -30°C (mPa.s)	D-5293	5995
Sulphated Ash(mass%)	D-874	1.15
Sulphur Content (mass%)	D-4294	0.30
Phosphorus (P) (mass%)	D-5185	0.09
HTHS at 150°C (mPa.s)	D-5481	3.21

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit www.benzollubricants.de

