INDUSTRIAL GEAR OIL EP ISO 460



Description

BENZOL® Industrial Gear Oil EP ISO 460 premium quality oils manufactured from high quality base stocks fortified with extreme pressure additives, antifoam, antirust and antioxidation agents, thereby they have excellent oxidation resistance and thermal stability. BENZOL® Industrial Gear Oil is formulated to protect gear teeth from wear at its earliest stages.



Applications

BENZOL® Industrial Gear oil is recommended for all heavy-duty enclosed gear drives with circulation or splash lubrication system operating under heavy or shock load conditions, plain and antifriction bearings subjected to shock and heavy loads. BENZOL® Industrial Gear oil is used in a wide range of industrial and marine applications, especially spur, helical, bevel and worm gearing.

Specifications and Approvals

AGMA 9005-E02, ISO 12925-1 Typ, DIN 51517-3 CLP: 2009-06. AIST 224.

Technical Specifications

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	L3.5
Density @ 15 °C, Kg/L	D-1298	0.8922
Viscosity @ 100 °C, cst	D-445	30.77
Viscosity @ 40 °C, cst	D-445	460
Viscosity index	D-2270	96

Performance Benefits

- Resistance to oxidation, ageing and sludge formation.
- Improved bearing life resulting in higher productivity.
- Outstanding protection to rust and corrosion of copper alloys.
- Maintains protective lubricant film in all operating conditions.
- Cleaner systems and reduced maintenance.

4 x 5

12 x 1

1 x 20

1 x 200

1x1000

• Easy water separation.

IG13000331

IG13000171

IG13000511

IG13000561

IG13000601

Product/Part Number

• Less gear and bearing wear resulting in less unexpected downtime

IG13000321

IG13000171

IG13000531

IG13000571

4 x 4

24 X 1

1 x 25

1 x 208

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	L3.5
Density @ 15 °C, Kg/L	D-1298	0.8922
Viscosity @ 100 °C, cst	D-445	30.77
Viscosity @ 40 °C, cst	D-445	460
Viscosity index	D-2270	96
Flash Point, °C (COC)	D-92	264
Pour Point, °C	D-97	-15
Foam SEQ.I/II/III	D-892	0/0/0

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit www.benzollubricants.de

