

SHPD FLEET TURBO SAE 10W40 API CI-4/SL ACEA E7



Description

BENZOL® SHPD FLEET TURBO SAE 10W40 API CI-4/SL uses Synthetic technology base oils and balanced additive system to deliver fuel economy performance, and to protect modern engines operating under extreme conditions of pressures and temperatures. It is the ideal choice for operators of heavy-duty truck and bus fleets equipped with latest emission designs.



Applications

BENZOL® SAE 10W40 API CI-4/SL is particularly suitable for use in naturally aspirated and turbocharged diesel engines in the trucks of haulage transport, in bus transport, in construction and ship transport. It is also suitable for light commercial vehicles with diesel engines.

Specifications and Approvals

API CI-4/SL, ACEA E7, MB 228.3/MB 229.1, Volvo VDS-3, Renault VI RLD-2, Cummins CES 20076/7/20078, Deutz DQC –III-05.

Performance Benefits

- Total engine protection.
- Outstanding oxidation & thermal stability.
- Drain interval extension.
- Help reduce oil consumption
- Excellent lubricity at both high and low temperatures
- Protection against foaming, rust, and oxidation in the Engines.

Product/Part Number

FT10543332	4 x 5	FT10543322	4 x 4
FT10543172	12 x 1	FT10543172	24 X 1
FT10543512	1 x 20	FT10543532	1 x 25
FT10543562	1 x 200	FT10543572	1 x 208
FT10543602	1x1000		

Technical Specifications

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	L2.5
Density @ 15 °C, kg/L	D-1298	0.8650
Viscosity @ 100 °C, cSt	D-445	14.50
Viscosity @ 40 °C, cSt	D-445	102.9
Viscosity index	D-2270	145
Flash Point, °C (COC)	D-92	230
Pour Point, °C	D-97	-33
Foam SEQ.I/II/III	D-892	0/0/0
TBN, mg KOH/g	D-2896	10.3
CCS at -25°C (mPa.s)	D-5293	6590
Sulphated Ash(mass%)	D-874	1.25
Sulphur Content (mass%)	D-4294	0.32
Phosphorus (P) (mass%)	D-5185	0.12

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit www.benzollubricants.de

