# **EFFICIENT DRIVE SAE 10W40 API SN/CF ACEA A3/B4**



## Description

**BENZOL®** Efficient Drive SAE 10W40 API SN/CF is a high range quality lubricant, synthetic, specially formulated to meet the latest performance requirements of modern engines. It can be used in city, road and highway, under extreme conditions in all seasons.



### **Applications**

**BENZOL®** Synthetic SAE 10W40 Engine Oil is recommended for passenger cars, light trucks, gasoline powered equipment engines. For all-season use in engines operating on gasoline, high-ethanol gasoline and without turbo-charging and direct injection.

# **Specifications and Approvals**

API SN/CF, ACEA A3/B4, MB 229.5, RN 0700/0710, VW 501.00/ 505.00, FIAT 9.55535-D2/G2, PSA B71 2300

## **Technical Specifications**

### **Performance Benefits**

- Enhanced fuel economy properties.
- Excellent anti-wear characteristics.
- Excellent low temperature capabilities.

1x1000

Increase engine efficiency.

ED10624602

Advanced synthetic formula

| Product/Part Number |          |        |           |         |  |
|---------------------|----------|--------|-----------|---------|--|
| ED106243            | 32 4 x 5 | 5 EI   | D10624326 | 4 x 4   |  |
| ED106241            | 72 12 x  | :1 EI  | D10624172 | 24 X 1  |  |
| ED106245            | 12 1 x 2 | 20 EI  | D10624532 | 1 x 25  |  |
| ED106245            | 62 1 x 2 | 200 EI | D10624572 | 1 x 208 |  |

| Tests                   | Method    | Results        |
|-------------------------|-----------|----------------|
| Appearance              | Visual    | Clear & Bright |
| Water                   | Hot Plate | Nil            |
| Color                   | D-1500    | L2.5           |
| Density @ 15 °C, kg/L   | D-1298    | 0.8675         |
| Viscosity @ 100 °C, cSt | D-445     | 14.85          |
| Viscosity @ 40 °C, cSt  | D-445     | 100.3          |
| Viscosity index         | D-2270    | 155            |
| Flash Point, °C (COC)   | D-92      | 230            |
| Pour Point, °C          | D-97      | -36            |
| Foam SEQ.I/II/III       | D-892     | 0/0/0          |
| TBN, mg KOH/g           | D-2896    | 10.2           |
| CCS at -25°C (mPa.s)    | D-5293    | 6450           |

## **HEALTH AND SAFETY**

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit <a href="https://www.benzollubricants.de">www.benzollubricants.de</a>

