

TRANS DRIVE ATF ULV



Description

BENZOL® Trans Drive ATF ULV is formulated with premium synthetic base stocks and advanced special performance additive technology which delivers better shift performance. It is designed with high quality hydrotreated oils and special additive package to meet the demands of today's electronic transmissions requiring ultra-low viscosity (ULV) fluid which provides superior fluid flow under high and low temperature conditions. Benzol ULV ATF consistently provide your car/light truck transmission longer service life.



Applications

BENZOL® Trans drive ATF ULV is particularly recommended for use in automatic transmissions of Passenger car & light duty trucks that require a FORD Mercon & GM Dexron ULV fluid. It is also suitable for use in the vehicles using latest speed 9 & 10 transmissions, including Ford F-150 and Raptor 10R80 trucks.

Specifications and Approvals

Ford MERCON ULV, WSS-M2C949-A, XT-12-ULV, GM 19352619, GM 19352620, GM DEXRON ULV ATF, BMW 83 22 2 413 477 (ATF7), Audi G 053 001, G 060 540, Volvo 31 492 172, 31 492 173, MB 236.15 (except FE benefits), MB 236.16 (Except FE benefits), MB 236.17 (Except FE benefits)

Performance Benefits

- Exceptional oxidation behavior.
- Smoother shifts over a long period of time.
- Excellent Antiwear protection
- Low foaming tendency
- Compatible with all common seal materials
- Provides anti shudder durability
- Reliable protection against wear, sludge, adhesion and Corrosion

Product/Part Number

TD10000333	4 x 5	TD10000323	4 x 4
TD10000173	12 x 1	TD10000173	24 X 1
TD10000513	1 x 20	TD10000533	1 x 25
TD10000563	1 x 200	TD10000573	1 x 208
TD10000603	1x1000		

Technical Specifications

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	Red
Density @ 15 °C, kg/L	D-1298	0.8450
Viscosity @ 100 °C, cSt	D-445	4.50
Viscosity @ 40 °C, cSt	D-445	27.61
Viscosity index	D-2270	170
Flash Point, °C (COC)	D-92	216
Pour Point, °C	D-97	-51
Foam SEQ.I/II/III	D-892	0/0/0
Brookfield viscosity@-40°C, cP	D-2983	4600

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit www.benzollubricants.de

