

HD FLEET SAE 70 API CF ACEA E2



Description

BENZOL® HD Fleet SAE 70 ACEA E2 is monograde mineral motor oil, recommended for the lubrication of all types of heavy-duty diesel engines with or without turbocharging, heavy duty vehicle engines, engines in agricultural, construction and mining industry.



Applications

BENZOL® HD Fleet SAE 70 can be used in older trucks and buses as well as for cost effective lubrication in off-highway applications such as agricultural tractors.

Specifications and Approvals

API CF/SF, ACEA E2.

Technical Specifications

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	L3.0
Density @ 15 °C, kg/L	D-1298	0.8862
Viscosity @ 100 °C, cSt	D-445	26.50
Viscosity @ 40 °C, cSt	D-445	296.1
Viscosity index	D-2270	118
Flash Point, °C (COC)	D-92	240
Pour Point, °C	D-97	-18
Foam SEQ.I/II/III	D-892	0/0/0
TBN, mg KOH/g	D-2896	7.2

Performance Benefits

- High thermal and oxidation stability.
- Fuel economy and better cold starting.
- Good detergent and dispersant qualities.
- Excellent engine cleanliness and wear protection.
- Maintains engine power and efficiency and lowers servicing costs.

Product/Part Number

HD23201331	4 x 5	HD23201321	4 x 4
HD23201171	12 x 1	HD23201171	24 X 1
HD23201511	1 x 20	HD23201531	1 x 25
HD23201561	1 x 200	HD23201571	1 x 208
HD23201601	1x1000		

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit www.benzollubricants.de

