

BRAKE FLUID DOT-3



Description

BENZOL® Brake fluid DOT-3 is a premium quality type of hydraulic fluid used in hydraulic brake and clutch applications in automobiles, motorcycles, light trucks, and some bicycles. It is used to transfer force into pressure. It is recommended for complete fluid replacement and "top-up" in most cars and light trucks.



Applications

BENZOL® Brake Fluid is formulated for use in automotive disc brake systems and all hydraulic brake systems with the exception of those where a mineral oil-based fluid is required. It is suitable for use where the vehicle manufacturer specifies DOT-3 fluids.

Specifications and Approvals

SAE J1703, J1704, FMVSS No. 116 DOT 3 MOTOR VEHICLE BRAKE FLUID

Performance Benefits

- Unique Low Moisture Activity (LMA) formulation provides maximum wet boiling point protection against vapor lock brake failure when compared to leading brake fluids.
- Provides superior fluidity at low temperatures for optimum braking response.
- Mixes with conventional brake fluid.

Product/Part Number

BF01000170	12 x 1	BF01000100	24 x 500
BF01000030	24 X 250		

Technical Specifications

Tests	Method	Results
Appearance	Visual	Transparent
Equilibrium reflux boiling point (ERBP), °C	FMVSS 116	245
Wet equilibrium reflux boiling point (WERBP), °C	FMVSS 116	150
Kinematic Viscosity@ 100°C, cSt	ASTM D-445	2.10
Kinematic Viscosity@ -40°C, cSt	ASTM D-445	1200
pH	FMVSS 116	8.5
Specific Gravity 60 °F	ASTM D-1298	1.060
Flash Point, °C	ASTM D-92	125

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other **BENZOL** products, please visit www.benzollubricants.de

