

HD FLEET SAE 60 API CF ACEA E2



Description

BENZOL® HD Fleet SAE 60 ACEA E2 is an alloyed, mineral-oil-based monograde diesel oil. Selected base oils in combination with ideally coordinated additives provide optimal protection against wear and oxidation. High-quality detergent additives dissolve dirt and deposits and guide these to the oil filter with the help of select dispersants.



Applications

BENZOL® HD Fleet SAE 60 can be used in older trucks and buses as well as for cost effective lubrication in off-highway applications such as agricultural tractors.

Specifications and Approvals

API CF/SF, ACEA E2.

Technical Specifications

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	2.5
Density @ 15 °C, kg/L	D-1298	0.8850
Viscosity @ 100 °C, cSt	D-445	24.50
Viscosity @ 40 °C, cSt	D-445	268.2
Viscosity index	D-2270	116
Flash Point, °C (COC)	D-92	246
Pour Point, °C	D-97	-18
Foam SEQ.I/II/III	D-892	0/0/0
TBN, mg KOH/g	D-2896	7.2

Performance Benefits

- Excellent protection against piston deposits.
- Controls engine wear.
- Good oxidation and thermal stability.
- Excellent engine cleanliness and wear protection.
- Maintains engine power and efficiency and lowers servicing costs.

Product/Part Number

HD22201331	4 x 5	HD22201321	4 x 4
HD22201171	12 x 1	HD22201171	24 X 1
HD22201511	1 x 20	HD22201531	1 x 25
HD22201561	1 x 200	HD22201571	1 x 208
HD22201601	1x1000		

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit www.benzollubricants.de

