

# HD FLEET SAE 60 API CH-4 ACEA E5



## Description

**BENZOL®** HD Fleet SAE 60 API CH-4 is a superior quality heavy-duty monograde lubricant for diesel engines. It is blended from premium quality virgin base oils and advanced additives that offer the best possible lubrication. It assures excellent protection against high temperature engine deposits, oil degradation, and forms a thick oil film that protects engine parts from friction and wear.



## Applications

**BENZOL®** HD Fleet SAE 60 can be used in older trucks and buses as well as for cost effective lubrication in off-highway applications such as agricultural tractors.

## Specifications and Approvals

API CH-4, ACEA E5, MB-Approval 228.0, MAN 270, MIL-L 2104 E, MTU Oil Type 1.

## Technical Specifications

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	2.5
Density @ 15 °C, kg/L	D-1298	0.8845
Viscosity @ 100 °C, cSt	D-445	24.55
Viscosity @ 40 °C, cSt	D-445	260.5
Viscosity index	D-2270	120
Flash Point, °C (COC)	D-92	248
Pour Point, °C	D-97	-18
Foam SEQ.I/II/III	D-892	0/0/0
TBN, mg KOH/g	D-2896	10.4

## Performance Benefits

- Excellent protection against piston deposits.
- Controls engine wear.
- Good oxidation and thermal stability.
- Excellent engine cleanliness and wear protection.
- Maintains engine power and efficiency and lowers servicing costs.

## Product/Part Number

HD22402331	4 x 5	HD22402321	4 x 4
HD22402171	12 x 1	HD22402171	24 X 1
HD22402511	1 x 20	HD22402531	1 x 25
HD22402561	1 x 200	HD22402571	1 x 208
HD22402601	1x1000		

## HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit [www.benzollubricants.de](http://www.benzollubricants.de)

