

# GEAR SHIFT SAE 140 API GL-4



## Description

**BENZOL®** Gear Shift SAE 140 API GL-4 hypoid Gear Oil has low pour points and high temperature properties to provide lubrication over a wide temperature range. This versatile lubricant contains anti-rust and anti-wear EP additives to provide the corrosion protection in drives and hypoid gears.



## Applications

**BENZOL®** Gear Shift SAE 140 is particularly suitable for all hypoid transmissions and is also suitable for spiral bevel gear, worm wheels and most transaxles.

## Specifications and Approvals

API GL-4, MIL-L2105B

## Technical Specifications

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	L3.0
Density @ 15 °C, kg/L	D-1298	0.8855
Viscosity @ 100 °C, cSt	D-445	26.85
Viscosity @ 40 °C, cSt	D-445	325.1
Viscosity index	D-2270	110
Flash Point, °C (COC)	D-92	240
Pour Point, °C	D-97	-18
Foam SEQ.I/II/III	D-892	0/0/0

## Performance Benefits

- Good lubricating characteristics provide stable oil film and reduce wear.
- Prevents premature failure of transmission parts.
- Outstanding frictional durability.
- Reduced wear and maintenance costs.
- Excellent viscosity-temperature properties.
- Optimal cold flow property.

## Product/Part Number

GS10020331	4 x 5	GS10020321	4 x 4
GS10020171	12 x 1	GS10020171	24 X 1
GS10020511	1 x 20	GS10020531	1 x 25
GS10020561	1 x 200	GS10020571	1 x 208
GS10020601	1x1000		

## HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit [www.benzollubricants.de](http://www.benzollubricants.de)

