

GEAR SHIFT SAE 75W API GL-5



Description

BENZOL® Gear Shift SAE 75W API GL-5 is a premium lubricating oil for mechanical transmissions, formulated with high quality special refined and synthetic base oils and special EP-additives to give the maximum performance.



Applications

BENZOL® Gear Shift SAE 75W is particularly suitable for all hypoid transmissions and is also suitable for spiral bevel gear, worm wheels and most transaxles.

Specifications and Approvals

API GL-5, BMW 23007533819/23007533513, MTF LT-5, 83227533818, FIAT 9.55550-MZ2, 9.55550-SA1, Ford WSS-M2C200-E1/D3, GM MTF BOT 0063/1940004, MB 235.71/A 002 989 04 03, PSA 9730 A8, VW G 070 726/N 05279800

Technical Specifications

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	L2.5
Density @ 15 °C, kg/L	D-1298	0.8675
Viscosity @ 100 °C, cSt	D-445	6.5
Viscosity @ 40 °C, cSt	D-445	37.05
Viscosity index	D-2270	130
Flash Point, °C (COC)	D-92	220
Pour Point, °C	D-97	-48
Foam SEQ.I/II/III	D-892	0/0/0
Brookfield Viscosity@-40°C, cP	D-2983	42500

Performance Benefits

- Superior protection against rust and corrosion.
- Does not break down in stop and go driving.
- Low viscosity characteristics optimize transmission efficiency and fuel Economy.
- Contributes to easy and smooth shifting, and quick starts
- Helps to control operating costs and contribute to productivity
- Contributes to long seal life, and to extended drain and service intervals

Product/Part Number

GS01030333	4 x 5	GS01030323	4 x 4
GS01030173	12 x 1	GS01030173	24 X 1
GS01030513	1 x 20	GS01030533	1 x 25
GS01030563	1 x 200	GS01030573	1 x 208
GS01030603	1x1000		

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit www.benzolubricants.de

