

HIGH TEMPERATURE GREASE EP-2



Description

BENZOL® High temperature Grease EP-2 is non-melting, Bentonite clay-thickened grease with EP and anti-rust additive. This grease is non-soap type which shows outstanding heat resistance as its thickener is non-melting.



Applications

BENZOL® High Temperature Grease is recommended for general industrial applications requiring grease that does not melt where continuous high temperatures or intermittent very-high temperatures are experienced.

Specifications and Approval

ISO 6743-9: L-XBCEB-2 DIN 51 502: KP2K -15

Technical Specifications

Tests	Method	Results
NLGI Grade	-	2
Soap	-	Lithium
Appearance	Visual	Buttery & Smooth
Color	Visual	Blue
Penetration, worked@25°C, 0.1mm	ASTM D217	280
Dropping Point, °C	ASTM D566	Not Applicable
Corrosion Prevention	ASTM D1743	Pass
Operating Temperature	-	-15°C to +120°C

Performance Benefits

- Good mechanical stability.
- Good extreme pressure and anti-wear properties provide the potential for prolonged component life.
- Acts as a protective layer on exposed parts.
- Excellent resistant to oxidation, rust and Corrosion.
- Clings to bearing surfaces.
- Smooth texture.

Product/Part Number

HG02050120	24 x 500	HG02050180	24 x 1
HG02050410	1 x 15	HG02050610	1 x 180

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL product, please visit www.benzollubricants.de

