

2T SUPER MARINE SAE 30 API TC-W2



Description

BENZOL® 2T Super Marine Outboard Oil SAE 30 API TC-W2 offers the maximum protection available for modern high temperature outboard engines and its formulation also provides outstanding performance when used in 2 stroke engines.



Applications

BENZOL® 2T Super Marine Outboard oil is developed for two-stroke engines operating under a range of varied conditions. It is recommended for use in the applications for air cooled 2-stroke engines light motorbikes and scooters.

Specifications and Approvals

API TC, NMMA TC-W2

Technical Specifications

Performance Benefits

- Mixes easily with fuel for pre-mix applications.
- Complete and quick miscibility with petrol.
- Exceptional lubricating capacity, preventing piston seizure.
- High anti-wear capacity.
- Reduced Maintenance Costs.
- Approved for use with most ethanol blended fuels
- Outstanding results in reducing visible smoke and particle emissions.

Product/Part Number

OF18020331	4 x 5	OF18020321	4 x 4
OF18020171	12 x 1	OF18020171	24 X 1
OF18020511	1 x 20	OF18020531	1 x 25
OF18020561	1 x 200	OF18020571	1 x 208
OF18020601	1x1000		

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	Green/Blue
Density @ 15 °C, kg/L	D-1298	0.8785
Viscosity @ 100 °C, cSt	D-445	11.35
Viscosity @ 40 °C, cSt	D-445	78.80
Viscosity index	D-2270	135
Flash Point, °C (COC)	D-92	200
Pour Point, °C	D-97	-36
Foam SEQ.I/II/III	D-892	0/0/0
TBN, mg KOH/g	D-2896	4.9
Sulphated Ash, %	D-874	<0.01

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit www.benzollubricants.de

