

# 4T MOTO RACER SAE 10W30 API SN JASO MB



## Description

**BENZOL®** 4T Moto Racer 10W30 API SN is a synthetic motorcycle oil specially designed to meet today's 4-Stroke scooter specifications where JASO MB specification is required. JASO MB lubricant ensures optimal engine performance and fuel economy on all scooters without wet clutch.



## Applications

**BENZOL®** 4T Moto Racer is suitable for all makes of 4-stroke bikes, both carbureted and fuel injected where API SN (or below) and JASO MB recommended. It has been especially developed for use in all motorcycles with medium to large engines

## Specifications and Approvals

API SN, JASO MB

## Performance Benefits

- The trials in four-stroke motorcycles under extreme working Conditions have confirmed excellent protection against wear.
- Ensures full protection for the engine.
- Exceptional thermo-oxidative stability.
- Great durability at high temperature.
- Quick engine response and improved power output and increased reliability.

## Product/Part Number

|            |         |            |         |
|------------|---------|------------|---------|
| 4T09601332 | 4 x 5   | 4T09620323 | 4 x 4   |
| 4T09601172 | 12 x 1  | 4T09620173 | 24 x 1  |
| 4T09601512 | 1 x 20  | 4T09610532 | 1 x 25  |
| 4T09620563 | 1 x 200 | 4T09620573 | 1 x 208 |
| 4T09601602 | 1x1000  |            |         |

## Technical Specifications

| Tests                   | Method    | Results        |
|-------------------------|-----------|----------------|
| Appearance              | Visual    | Clear & Bright |
| Water                   | Hot Plate | Nil            |
| Color                   | D-1500    | L2.5           |
| Density @ 15 °C, kg/L   | D-1298    | 0.8660         |
| Viscosity @ 100 °C, cSt | D-445     | 10.75          |
| Viscosity @ 40 °C, cSt  | D-445     | 68.25          |
| Viscosity index         | D-2270    | 148            |
| Flash Point, °C (COC)   | D-92      | 232            |
| Pour Point, °C          | D-97      | -36            |
| Foam SEQ.I/II/III       | D-892     | 0/0/0          |
| TBN, mg KOH/g           | D-2896    | 7.40           |
| CCS at -25°C (mPa.s)    | D-5293    | 6470           |

## HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit [www.benzollubricants.de](http://www.benzollubricants.de)

