

4T MOTO RACER 15W50 API SN JASO MA2



Description

BENZOL® 4T Moto Racer SAE 15W50 API SN is a premium performance, shear-stable, multi-grade gasoline engine oil specifically designed for use in four-stroke motorcycles and portable power equipment requiring API SN JASO MA/MA2 Lubricants, including high output engines operating in severe service



Applications

BENZOL® 4T SAE 15W50 is used for motorcycles and scooters in city traffic. It is suitable for all types of four stroke motorcycles where JASO MA 2 performance is recommended.

Specifications and Approvals

API SN, JASO MA2.

Technical Specifications

Performance Benefits

- Improved control of sludge and oil thickening.
- Vastly improved protection of gears.
- Exceptional thermo-oxidative stability.
- Complies with requirements of catalyst equipped engines.
- High friction factor prevents clutch slippage and disc wear.

Product/Part Number

4T14620332	4 x 5	4T14620322	4 x 4
4T14620172	12 x 1	4T14620172	24 X 1
4T14620512	1 x 20	4T14620532	1 x 25
4T14620562	1 x 200	4T14620572	1 x 208
4T14620602	1x1000		

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	L2.5
Density @ 15 °C, Kg/L	D-1298	0.8715
Viscosity @ 100 °C, cst	D-445	19.35
Viscosity @ 40 °C, cst	D-445	167.5
Viscosity index	D-2270	132
Flash Point, °C (COC)	D-92	236
Pour Point, °C	D-97	-33
Foam SEQ.I/II/III	D-892	0/0/0
TBN, mg KOH/g	D-2896	6.2
CCS at -20°C (mPa.s)	D-5293	6875

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit www.benzollubricants.de

