

4T MOTO RACER SAE 20W50 API SN JASO MB



Description

BENZOL® 4T Moto Racer 20W50 API SN is a premium quality mineral motorcycle oil added specially selected performance additives to provide excellent protection for Engine. Besides lowering the maintenance cost, it enhances the engine life with less wear and tear and ensures longer drain period with enhanced fuel economy.



Applications

BENZOL® 4T Moto Racer is especially developed for use in all motorcycles with medium to large engines. It should only be used when this SAE 20W50 viscosity level is recommended by the manufacturer of the motorcycle.

Specifications and Approvals

API SN, JASO MB

Technical Specifications

Performance Benefits

- The trials in four-stroke motorcycles under extreme working Conditions have confirmed excellent protection against wear.
- Ensures full protection for the engine.
- Exceptional thermo-oxidative stability.
- Great durability at high temperature.
- Quick engine response and improved power output and increased reliability.

Product/Part Number

4T16601331	4 x 5	4T16601321	4 x 4
4T16601171	12 x 1	4T16601171	24 X 1
4T16601511	1 x 20	4T16601531	1 x 25
4T16601561	1 x 200	4T16601571	1 x 208
4T16601601	1x1000		

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	L2.5
Density @ 15 °C, kg/L	D-1298	0.8770
Viscosity @ 100 °C, cSt	D-445	19.60
Viscosity @ 40 °C, cSt	D-445	165.3
Viscosity index	D-2270	136
Flash Point, °C (COC)	D-92	234
Pour Point, °C	D-97	-27
Foam SEQ.I/II/III	D-892	0/0/0
TBN, mg KOH/g	D-2896	7.0
CCS at -15°C (mPa.s)	D-5293	8450

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit www.benzollubricants.de

