



# MODERN DRIVE SAE 5W40 API SN/CF ACEA A3/B4

## Description

**BENZOL®** Modern Drive SAE 5W40 API SN/CF is a high range quality lubricant, fully synthetic, specially formulated to meet the latest performance requirements of modern engines. It can be used in city, road and highway, under extreme conditions in all seasons.



## Applications

**BENZOL®** Fully Synthetic SAE 5W40 Engine Oil is recommended for passenger cars, light trucks, gasoline powered equipment engines. For all-season use in engines operating on gasoline, high-ethanol gasoline and without turbo-charging and direct injection.

## Specifications and Approvals

API SN/CF, ACEA A3/B4, MB 229.3/229.5, VW 502.00/505.00, BMW LL-01, RN 0700/0710, PORSCHE A40, PSA B71 2296, OPEL GM-LL-A-025, GM-LL-B-025, FIAT 9.55535-H2/M2/Z2

## Technical Specifications

| Tests                   | Method    | Results        |
|-------------------------|-----------|----------------|
| Appearance              | Visual    | Clear & Bright |
| Water                   | Hot Plate | Nil            |
| Color                   | D-1500    | L3.0           |
| Density @ 15 °C, kg/L   | D-1298    | 0.8510         |
| Viscosity @ 100 °C, cSt | D-445     | 14.15          |
| Viscosity @ 40 °C, cSt  | D-445     | 87.40          |
| Viscosity index         | D-2270    | 168            |
| Flash Point, °C (COC)   | D-92      | 232            |
| Pour Point, °C          | D-97      | -39            |
| Foam SEQ.I/II/III       | D-892     | 0/0/0          |
| TBN, mg KOH/g           | D-2896    | 10.1           |
| CCS at -30°C (mPa.s)    | D-5293    | 6150           |
| Sulphated Ash(mass%)    | D-874     | 1.2            |
| Sulphur Content (mass%) | D-4294    | 0.28           |
| Phosphorus (P) (mass%)  | D-5185    | 0.080          |
| HTHS at 150°C (mPa.s )  | D-5481    | 3.65           |

## Performance Benefits

- Enhanced fuel economy properties.
- Excellent anti-wear characteristics.
- Excellent low temperature capabilities.
- Increase engine efficiency.
- Advanced synthetic formula.

## Product/Part Number

|            |         |            |         |
|------------|---------|------------|---------|
| MD07624333 | 4 x 5   | MD07624323 | 4 x 4   |
| MD07624173 | 12 x 1  | MD07624173 | 24 X 1  |
| MD07624513 | 1 x 20  | MD07624533 | 1 x 25  |
| MD07624563 | 1 x 200 | MD07624573 | 1 x 208 |
| MD07624603 | 1x1000  |            |         |

## HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit [www.benzollubricants.de](http://www.benzollubricants.de)

