

MODERN DRIVE SAE 5W40 API SN/CF ACEA C3



Description

BENZOL® Modern Drive SAE 5W40 API SN/CF is a high range quality lubricant, fully synthetic, specially formulated to meet the latest performance requirements of modern gasoline and diesel engines. It can be used in city, road and highway, under extreme conditions in all seasons.



Applications

BENZOL® Fully Synthetic SAE 5W40 Engine Oil is recommended for passenger cars, light trucks, gasoline powered equipment engines. For all-season use in engines operating on gasoline, high-ethanol gasoline and with or without turbo-charging and direct injection.

Specifications and Approvals

API SN/CF, ACEA C2/C3, MB 229.31/229.51/229.52/226.5, VW 502.00/505.00, BMW LL-04, GM Dexos 2, PORSCHE A40, RN 0700/0710, FIAT 9.55535-S2, FORD WSS-M2C917-A

Technical Specifications

Performance Benefits

- Outstanding low temperature capabilities.
- Incorporate low ash foaming additive to extend DPF (Diesel Particulate Filters) service lifetime.
- Low Sulphur and Phosphorous content help to reduce poisoning of Gasoline Catalytic Converters (CAT's).
- Reduces engine deposits to help maximize engine response.

Product/Part Number

MD07627333	4 x 5	MD07627323	4 x 4
MD07627173	12 x 1	MD07627173	24 X 1
MD07627513	1 x 20	MD07627533	1 x 25
MD07627563	1 x 200	MD07627573	1 x 208
MD07627603	1x1000		

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	L3.0
Density @ 15 °C, kg/L	D-1298	0.8525
Viscosity @ 100 °C, cSt	D-445	14.35
Viscosity @ 40 °C, cSt	D-445	86.3
Viscosity index	D-2270	173
Flash Point, °C (COC)	D-92	232
Pour Point, °C	D-97	-36
Foam SEQ.I/II/III	D-892	0/0/0
TBN, mg KOH/g	D-2896	6.7
CCS at -30°C (mPa.s)	D-5293	6200
Sulphated Ash(mass%)	D-874	0.76
Sulphur Content (mass%)	D-4294	0.25
Phosphorus (P) (mass%)	D-5185	0.080
HTHS at 150°C (mPa.s)	D-5481	3.60

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit www.benzollubricants.de

